



# SAFETY DATA SHEET

## 1. Identification

**Product number** 100009083  
**Product identifier** 17 OZ TERAND VAND MARK REMOVER LB 12PK  
**Company information** CPC  
1005 S. Westgate Drive  
Addison, IL 60101 United States  
**Company phone** General Assistance 630-543-7600  
**Emergency telephone US** 1-866-836-8855  
**Emergency telephone outside US** 1-952-852-4646  
**Version #** 01  
**Recommended use** Not available.  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Skin corrosion/irritation Category 2  
Reproductive toxicity Category 1A  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Specific target organ toxicity, repeated exposure Category 2  
Aspiration hazard Category 1  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Not classified.

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2  
Hazardous to the aquatic environment, long-term hazard Category 2

### Supplemental information

**Hazard statement** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Prevention** Avoid release to the environment.

**Response** Collect spillage.

29.23% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 29.23% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

### 3. Composition/information on ingredients

#### Mixtures

Hazardous components Chemical name	Common name and synonyms	CAS number	%
Toluene		108-88-3	40 - 60
Butane		106-97-8	10 - 20
Isopropyl Alcohol		67-63-0	2.5 - 10
Propane		74-98-6	2.5 - 10
Other components below reportable levels			20 - 40

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms/effects, acute and delayed</b>	Irritant effects. Prolonged exposure may cause chronic effects. May cause drowsiness or dizziness.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Water. Foam. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the MSDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

**Environmental precautions** Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

**Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid contact during pregnancy/while nursing. Avoid prolonged exposure. Use only in well-ventilated areas. Use personal protective equipment as required. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains.

**Conditions for safe storage, including any incompatibilities** Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3
Propane (CAS 74-98-6)	PEL	400 ppm
		1800 mg/m3 1000 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm	
		1225 mg/m3	
Isopropyl Alcohol (CAS 67-63-0)	TWA	500 ppm 980 mg/m3	
		400 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm	
		400 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm	
		TWA	375 mg/m3 100 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Toluene (CAS 108-88-3)

Skin designation applies.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Hand protection**

Wear protective gloves.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Color**

White.

**Form**

Aerosol.

**Physical state**

Gas.

**Flash point**

-156.00 °F (-104.44 °C) Propellant estimated

**Melting point/freezing point**

Not available.

**Odor**

Solvent.

**pH**

Not available.

**Solubility(ies)**

Not available.

**Vapor density**

Not available.

**Vapor pressure**

35 - 55 psig @70F estimated

**Viscosity**

Not available.

**Other information****Specific gravity**

0.728 estimated

**10. Stability and reactivity****Reactivity**

The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**

Material is stable under normal conditions.

**Possibility of hazardous reactions**

Hazardous polymerization does not occur.

**Conditions to avoid**

Avoid temperatures exceeding the flash point.

**Hazardous decomposition products**

No hazardous decomposition products are known.

**11. Toxicological information****Information on likely routes of exposure****Ingestion**

May be fatal if swallowed and enters airways.

**Inhalation**

May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects. May cause damage to organs by inhalation.

**Skin contact**

Causes skin irritation.

**Eye contact**

Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.

**Information on toxicological effects****Acute toxicity**

May be fatal if swallowed and enters airways. Narcotic effects.

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
17 OZ TERAND VAND MARK REMOVER LB 12PK (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	21454.5352 mg/kg, estimated 27.5383 ml/kg, estimated
	Rat	15293.3408 mg/kg, estimated
<i>Inhalation</i>		
LC50	Mouse	10390.0605 mg/l, 8 Hours, estimated 4931.1855 mg/l, 2 Hours, estimated 781.2283 mg/l, 24 Hours, estimated
	Rat	52146.9922 mg/l, If <1L: Consumer Commodity Hours, estimated 23827.4648 mg/l, 2 Hours, estimated 23288.959 mg/l, 15 Minutes, estimated 15624.5674 mg/l, 4 Hours, estimated 24.7142 mg/l/4h, estimated
<i>Oral</i>		
LD50	Dog	85643.8906 mg/kg, estimated
	Guinea pig	45885.2852 g/kg, estimated
	Mouse	56022.2852 mg/kg, estimated
	Rabbit	89.6245 g/kg, estimated
	Rat	4.7879 g/kg, estimated
<i>Other</i>		
LD50	Mouse	10935.5566 ml/kg, estimated 114.7049 mg/kg, estimated
	Rat	2219.9934 mg/kg, estimated
<b>Components</b>	<b>Species</b>	<b>Test Results</b>

**Butane (CAS 106-97-8)****Acute***Inhalation*

LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours

**Isopropyl Alcohol (CAS 67-63-0)****Acute***Dermal*

LD50	Rabbit	12800 mg/kg
------	--------	-------------

*Oral*

LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
	Rabbit	5.03 g/kg
	Rat	4.7 g/kg

*Other*

LD50	Mouse	1509 mg/kg
	Rat	1099 mg/kg

Components	Species	Test Results
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l/4h
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	5320 mg/l, 8 Hours 400 mg/l, 24 Hours
	Rat	26700 mg/l, If <1L: Consumer Commodity Hours 12200 mg/l, 2 Hours 8000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
<i>Other</i>		
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory sensitization</b>	Not available.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	May damage fertility or the unborn child.
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.
<b>Specific target organ toxicity - repeated exposure</b>	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
17 OZ TERAND VAND MARK REMOVER LB 12PK (CAS Mixture)		
Algae	IC50	Algae 800.1944 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia 14.9232 mg/l, 48 hours, estimated
Fish	LC50	Fish 48.7662 mg/l, 96 hours, estimated
Components	Species	Test Results
Isopropyl Alcohol (CAS 67-63-0)		
Algae	IC50	Algae 1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 13299 mg/L, 48 Hours

Components	Species	Test Results
<b>Aquatic</b>		
Fish	LC50	Bluegill (Lepomis macrochirus)
Toluene (CAS 108-88-3)		
Algae	IC50	Algae
Crustacea	EC50	Daphnia
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

Isopropyl Alcohol	0.05
Propane	2.36
Toluene	2.73
Butane	2.89

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**US RCRA Hazardous Waste U List: Reference**

Toluene (CAS 108-88-3)	U220
------------------------	------

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

**DOT**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1
<b>Subsidiary class(es)</b>	Not available.
<b>Packing group</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Labels required</b>	2.1
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	2.1
<b>Subsidiary class(es)</b>	-
<b>Packaging group</b>	Not available.

**Environmental hazards** Yes  
**Labels required** 2.1  
**ERG Code** Not available.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Packaging Exceptions** LTD QTY

**IMDG**

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, MARINE POLLUTANT  
**Transport hazard class(es)** 2.1  
**Subsidiary class(es)** -  
**Packaging group** Not available.  
**Environmental hazards**  
**Marine pollutant** Yes  
**Labels required** None  
**EmS** Not available.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Packaging Exceptions** LTD QTY

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.


**DOT**



**IATA; IMDG**



**Marine pollutant**



**15. Regulatory information**

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Toluene (CAS 108-88-3)

LISTED

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.



**SARA 304 Emergency release notification**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 % weight/volumn

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**Food and Drug Administration (FDA)** Not regulated.

**US state regulations****US. New Jersey Worker and Community Right-to-Know Act**

Butane (CAS 106-97-8) 500 lbs  
 Propane (CAS 74-98-6) 500 lbs  
 Toluene (CAS 108-88-3) 500 lbs

**US. Pennsylvania RTK - Hazardous Substances**

Butane (CAS 106-97-8)  
 Isopropyl Alcohol (CAS 67-63-0)  
 Propane (CAS 74-98-6)  
 Toluene (CAS 108-88-3)

**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reprod harm.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	06-30-2014
<b>Version #</b>	01
<b>Further information</b>	Not available.
<b>Disclaimer</b>	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
<b>Revision Information</b>	Physical & Chemical Properties: Multiple Properties Transport Information: Material Transportation Information