

TERAND

The Maintenance Professional's Choice

RTV SILICONE GASKET MAKER

116 - Black



This R.T.V. Sealant Adhesive can be used on metal, glass, porcelain, ceramics, wood, rubber, and most paint and plastics. As an instant gasket maker, this product replaces a wide range of cork, paper, asbestos, felt and metal gaskets. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink. Withstands intermittent temperatures up to 600°F and pressures up to 330 psi. Offers unmatched performance under the most severe operating conditions. Virtually unaffected by chemical deterioration, extreme weather, temperature or aging.



FEATURES

- Seals, Bonds, Insulates • Low Volatile • Flexible
- Easy to Use • Economical • Eliminates Waste
- Waterproof • Weatherproof
- Eliminates: Squeeze Tubes & Cartridge Guns
- 100% Low Volatile R.T.V. Silicone
- Meets G.M. and O.E.M. specifications
- Safe to use on oxygen sensor equipped vehicles

FOR USE ON

Pumps, High Pressure Pipe Joints, Oil and Transmission Pans, Oil and Water Pumps, Valve and Timing Chain Covers, Electric Motors and Electrical Control Boxes, Gear Boxes, Compressors, Machine Covers, Rigid Flange Assemblies, Equipment Housings

Characteristics:

Temperature Range	Cures at room temperature, range from -60°F to +600°F
Waterproof	Yes
Appearance	Black Paste
Shipping Weight	12 pounds

Seals, Bonds, Insulates
 Low Volatile • Flexible • Easy to Use
 Economical • Eliminates Waste
 Waterproof • Weatherproof
 Eliminates: Squeeze Tubes and Cartridge Guns
 100% Low Volatile R.T.V. Silicone
 Meets G.M. and O.E.M. specifications
 Safe to use on oxygen sensor equipped vehicles
 Pressurized dispenser makes any size or shape gasket instantly
 Remains permanently flexible at temperatures from -60°F to +500°F
 Eliminates need to stock conventional gaskets and seals
 Reduces down time - gets equipment back in operation fast

CAUTION: CONTACT WITH UNCURED SEALANT CAUSES IRRITATION. CONTENTS UNDER PRESSURE OUTER CONTAINER IS PRESSURIZED WITH A FLAMMABLE HYDROFLUOROCARBON PROPELLANT. DO NOT REMOVE RUBBER PLUG IN BOTTOM OF CONTAINER. SEE OTHER CAUTIONS ON BACK PANEL. KEEP OUT OF REACH OF CHILDREN.
 NET WT. 8 OZ. (227 Grams)

www.cpaeroscience.com
 (800) 327-1835

