

TERAND

The Maintenance Professional's Choice

SILICONE LUBRICANT FOOD GRADE 590

FOR INDUSTRIAL USE - NOT FOR RETAIL SALE - FOR USE IN THE MANUFACTURING PROCESS ONLY.

Contains: Dimethylpolysiloxane (Poly Dimethylsiloxane; Dimethyl Silicone Fluid) with viscosity over 300 centistokes is listed in FDA regulations as a lubricant with incidental food contact.

A heat stable, non-staining, pure, dry silicone film that lubricates moving parts in food processing and packaging plants. Ideal for use on tables, conveyors, heat sealing and slicing equipment. Dry silicone formula prevents jamming and production slowdown on bottling and packaging lines. Can also be used on a non-food contact surfaces of ovens and grills to prolong time between cleanings.



FEATURES

- Safe on Plastic
- Stops Sticking
- Heat Stable from -40°F to over 392°F
- Non-Chlorinated
- For Food Packaging and Processing Equipment



FOR USE BY

- Meat and Poultry Plants
- Packaging Plants
- Container Molding Operations
- Bottling Plants

Specs:

Can Size	20 oz.
Net Weight	11 oz. (312 g)
Shipping Weight	12 lbs.
Packaged	12 cans per case
Extender Tube	No

Regulatory:

Ozone Depleting Compounds	None
Recyclable Package	Yes
Flammable	Yes

Physical Characteristics:

Color	Colorless
Fragrance	Mild Solvent
Shelf Life	1 year +

www.cpaeroscience.com
(800) 327-1835

