

TERAND

The Maintenance Professional's Choice


RUBBERIZED COATING

654



Provides a super-thick, black, durable and flexible rubberized film. Seals and acoustically reduces unwanted sound and vibration. Protects metal parts against the harmful effects of water, salt, sand and road chemicals. Effective on metals, wood, roofing materials, tin, concrete, etc. Stays pliable in winter cold, will not sag, melt or drip in the summer heat. Resists cracking, peeling, and abrasion.

FOR USE BY: Roofing Contractors, Maintenance Crews, Building Supers, Plumbers, Auto And Diesel Repair Shops, Garages, Taxi Companies, Construction Companies, Machine Shops, Equipment Manufacturers, Air Conditioning Maintenance, Truck Fleet Maintenance, and Public Transportation Maintenance Operations.



FEATURES

- Protects Metal Surfaces Against Corrosion
- Provides a Flexible, Water-Tight Film
- Reduces Unwanted Sound and Vibration
- Fills In Minor Cracks and Voids
- Effective Over a Wide Temperature Range



FOR USE ON

Overlapping Seams, Gravel Stops, Chimney and Skylight Flashing, Vents and Pipe Flashing, Mobile Home and Camper Roof Seams, A/C Drip Pans, Gutters, Below-Grade Foundations, Minor Leak Repair, Automobiles.

SPECS

Container Size	20 OZ. AEROSOL
Net Fill Weight	16 OZ
Shipping Weight	16 LBS
Packaged	12 cans per case
PHYSICAL CHARACTERISTICS	
Color	Black Liquid
Fragrance	Petroleum odor
Shelf Life	1 Year +
REGULATORY	
Ozone Depleting Compounds	None
Recyclable Packaging	Yes
VOC Compliant CARB/OTC	Yes
CPSC Flame Extension	Required to be labeled as extremely flammable per 16 CFR 1500.
24 HOUR MEDICAL EMERGENCY	1-866-836-8855

www.cpaeroscience.com
(800) 327-1835

